



LEVELS OF QUALITY

The lubricant GTx LIGHT FE C2 5W-30 complies with the following international specifications:

- API SN SM/CF
- ACEA C2-12 A1/B1-12 A5/B5-12
- HONDA
- NISSAN - SUBARU
- FORD WSS M2C-950-A
- PSA B712290/B71 2312
- FIAT 9.55535.S1
- BMW LL-12 FE
- TOYOTA-LEXUS

DESCRIPTION

Duglas Oil GTx LIGHT FE C2 5W-30 is a 100% synthetic lubricant with low ash content (Low SAPS) produced at the highest formulation levels, designed to provide excellent performances in modern turbocharged petrol and diesel engines complying with the new EURO IV and EURO V emission regulations.

The modern formulation technology with low ash content allows the extension of life and maintaining the efficiency of emission reduction systems of petrol and diesel cars (DPF, TWC, FAP) unchanged.

Duglas Oil GTx LIGHT FE C2 5W-30 has been specifically designed to satisfy the latest ACEA C2 specifications and is recommended for motorizations fitted with particulate filtration systems, are maintenance-free and without fuel additives.

The low HTHS gives outstanding Fuel Economy (FE) properties to the lubricant, by ensuring a steady reduction in fuel consumptions.

TYPICAL FEATURES

SAE Scale	5W/30
Density at 15°C.Kg./dm3 ASTM D1298	0.850
Viscosity at 100°C.cSt ASTM D445	10.3
Viscosity Index ASTM D2270	158
Flammability V.A.°C ASTM D92	216
Pour Point °C ASTM D97	-36
S.A. ASTM D874	0.80
T.B.N. ASTM D2896	7.1

The above mentioned values are indicative of production average values and are not an integral part of the specification.

RAM.OIL S.p.A.

Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111

Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) - tel +39 081.31.70.911

P.IVA 00291350635 - Capitale Sociale € 12.000.000,00 int. vers.

info@ramoil.it - www.ramoil.it

