OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS

GTe SUPER FE 5W-20

GTe LINE
100% SYNTHETIC – HYBRID TECH

REV.2 of 05/2024

LEVELS OF QUALITY

Duglas Oil GTe SUPER FE 5W-20 complies with the following international specifications:

- API SN, CF
- API SP, SN Resource Conserving
- ACEA C6, C5
- GM dexos1 Gen2
- ILSAC GF-5, GF-6A
- FORD WSS-M2C948-A/B, 960-A1
- STJLR 03.5004

DESCRIPTION

Duglas Oil GTe SUPER FE 5W-20 is a 100% SYNTHETIC high performance engine oil developed to meet the new demands of a market that is heading towards increasingly compressed engines such as Ford EcoBoost®. The superior quality bases in combination with special additives ensure very fast lubricant distribution and optimized friction characteristics.

The very low level of HTHS denotes a marked care for the Fuel Economy. If we combine the latter with the content level of SAPS and compatibility with after-treatment systems, we obtain an extremely sensitive lubricant to emissions that fully supports the EURO VI specification. In Duglas Oil GTe SUPER FE 5W-20 all this is combined with careful cleaning of both deposits and sludge, with anticorrosive and anti-oxidative properties.

TYPICAL FEATURES*

SAE Scale		5W/20
Density at 15°C Kg/dm^3	ASTM D1298	0,836
Viscosity at 100°C cSt	ASTM D445	8,5
Viscosity Index	ASTM D2270	155
Flammability V.A.°C	ASTM D92	200
Pour Point °C	ASTM D97	-39
S.A.	ASTM D874	0,78
T.B.N.	ASTM D2896	8,2

*The above-mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.
Sede Legale: Riviera di Chiaia, 256 - 80121 Napoli (NA)
Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111
Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) – tel +39 081.31.70.911
P.IVA 00291350635 - Capitale Sociale € 16.000.000,00 int. vers.
info@ramoil.it – ramoil@pec.ramoil.it - www.ramoil.it