DUGLAS OIL

OLI MOTORE TRAZIONE LEGGERA / PASSENGER CAR ENGINE OILS

GTe LINE
100% SYNTHETIC – HYBRID TECH

# GTe HYBRID-TECH 0W-20

REV.4 of 05/2024

## LEVELS OF QUALITY

GTe HYBRID-TECH 0W-20 complies with the following international specifications:

- API SN PLUS, SN Resource Conserving
- API SP, SP Resource Conserving
- ILSAC GF-6A, GF-5
- ACEA C5, C6
- GM Dexos1 Gen2
- BMW LL-17 FE+
- PSA B71 2010
- CHRYSLER MS 6395
- MB 229.71
- STJLR.51.5122
- FORD WSS-M2C947-A/B1, WSS-M2C962-A1
- RENAULT RN17FE
- OPEL/VAUXHALL OV0401547
- VOLVO VCC RBS0-2AE
- FIAT 9.55535-GSX/DSX, 9.55535-CR1, 9.55535-DM1

## DESCRIPTION

GTe HYBRID-TECH 0W-20 is a 100% SYNTHETIC FUEL ECONOMY lubricant with low ash content (MID SAPS), designed to provide exceptional performance in ultra-modern supercharged and undersized ("downsized") hybrid engines (HEV and PHEV). The needs of the latter are met thanks to the LSPI (Low Speed Pre-Ignition) protection and the very low viscosity grade which also allows excellent performance even at the lowest temperatures.

GTe HYBRID-TECH 0W-20 has also been specifically designed to meet the recent OEM's specifications for engines with extended service intervals and maintenance-free particulate filtration systems without adding fuel additives, also meeting the EURO VI restrictions. GTe HYBRID-TECH 0W-20 guarantees excellent compatibility with biofuels for all new engines.

## TYPICAL FEATURES*

| SAE scale | | 0W-20 |
|---|---|---|
| Density a 15°C Kg/dm$^3$ | ASTM D1298 | 0,840 |
| Viscosity at 100°C cSt | ASTM D445 | 8,3 |
| Viscosity Index | ASTM D2270 | 170 |
| Flammability V.A. °C | ASTM D92 | 200 |
| Pour point °C | ASTM D97 | -42 |
| S.A. | ASTM D874 | 0,78 |
| T.B.N. | ASTM D2896 | 8,2 |

*The above-mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.
Sede Legale: Riviera di Chiaia, 256 - 80121 Napoli (NA)
Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111
Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) – tel +39 081.31.70.911
P.IVA 00291350635 - Capitale Sociale € 16.000.000,00 int. vers.
info@ramoil.it – ramoil@pec.ramoil.it - www.ramoil.it