WAY OIL

INDUSTRIAL LUBRICANTS

Rev.2 of 04/2021

LEVELS OF QUALITY

The lubricants of the series WAY OIL comply with the following levels of quality:

- ISO-L-HG
- CINCINNATI P-47, P-50, P-53
- DIN 51502 CGLP

DESCRIPTION

The series of Way Oil oils are especially recommended for the lubrication of guides and slides of machine tools used for precision works.
They are also suitable for the lubrication of centralized plants, where different viscosities do not coincide.
EP and anti-wear properties are excellent and ensure proper lubrication even under high sliding loads.

The lubricating effect on the metal-plastic contact is also good.
Furthermore, they ensure a good protection from rust and corrosion to all machine parts thanks to the formation of a strong lubricating film which avoids unpleasant dripping phenomenon with vertical guides.

TYPICAL FEATURES*

ISO VG	32	46	68	220
Density at 15°C Kg/dm^3 ASTM D1298	0,872	0,877	0,885	0,900
Viscosity at 40°C.cSt ASTM D445	28,8 to 5,2	41,4 to 50,6	61,2 to 74,8	198 to 242
Viscosity at 100°C.cSt ASTM D445	5	7	9	20
Viscosity Index ASTM D2270	105	105	105	95
Flammability V.A.°C ASTM D92	216	240	236	270
Pour Point °C ASTM D97	-15	-15	-12	-9
Neutralization No. mgKOH/g ASTM D 974	0.3	0.3	0.3	0.3

*The above-mentioned values are indicative of production average values and are not an integral part of the specification.

RA.M.OIL S.p.A.
Sede Legale: Riviera di Chiaia, 256 - 80121 Napoli (NA)
Stabilimento: Via Filichito, 28 - 80013 Casalnuovo (NA) - tel +39 081.51.95.111
Uffici: Via Enrico Mattei, 37 - 80013 Casalnuovo (NA) – tel +39 081.31.70.911
P.IVA 00291350635 - Capitale Sociale € 16.000.000,00 int. vers.
info@ramoil.it – ramoil@pec.ramoil.it - www.ramoil.it